



Artikelnummer Part number	a	b	c	$\varnothing d1$	$\varnothing d2$	$\varnothing d3$	$\varnothing d4$	MBK (kN)	F (kg)
837-0600-01*	M6	28	12	28	16	17	6	–	–
837-0600	M6	36	13	36	20	20	8-11	8,2	140
837-0800-01*	M8	36	13	36	20	20	8	–	–
837-0800	M8	36	13	36	20	20	8-11	8,2	140
837-1000-01*	M10	45	17	45	25	25	10	–	–
837-1000	M10	45	17	45	25	25	10-13	13,5	230
837-1200-01*	M12	53	21	54	30	30	12	–	–
837-1200	M12	53	21	54	30	30	12-15	20,0	340
837-1600	M16	62	27	63	35	35	14-17	41,2	700
837-2000	M20	71	30	72	40	40	16-19	70,6	1200
837-2400	M24	90	36	90	50	50	20-24	105,9	1800

Werkstoff 1.4401 | DIN 580 | geschmiedet
 *Ähnlich DIN 580 | gegossen und poliert
 MBK= Mindestbruchkraft
 F = Tragfähigkeit

Material AISI316 | DIN 580 | drop-forged,
 *casted and mirror polished
 MBK= Breaking load
 F = Working load limit
 All dimensions in millimeters.