


# EINE SEITE SPANNSCHLOSS MIT ÖSE, ANDERE SEITE ÖSE, VERPRESST\_ONE SIDE TURNBUCKLE WITH EYE, OTHER SIDE WITH EYE, SWAGED



| Artikelnummer<br>Part number | ø Seil<br>ø rope | Sk     | Gewinde<br>Thread | Spannweg<br>Adjustment | ø d1 | ø d2 | kl min | kN  |
|------------------------------|------------------|--------|-------------------|------------------------|------|------|--------|-----|
| IK 410-0200                  | 2                | 7 x 7  | M5                | +26   -43              | 5,5  | 5,5  | 256    | 2,2 |
| IK 410-0300                  | 3                | 7 x 7  | M6                | +28   -50              | 6,5  | 6,5  | 322    | 5   |
| IK 410-0400                  | 4                | 7 x 7  | M6                | +28   -50              | 8,5  | 6,5  | 349    | 8,9 |
| IK 410-0401                  | 4                | 7 x 7  | M8                | +34   -50              | 8,5  | 8,5  | 381    | 8,9 |
| IK 410-0500                  | 5                | 7 x 7  | M8                | +34   -50              | 10,5 | 8,5  | 406    | 14  |
| IK 410-0600                  | 6                | 7 x 7  | M10               | +30   -50              | 13   | 10,5 | 454    | 20  |
| IK 410-0800                  | 8                | 7 x 7  | M12               | +46   -70              | 14,5 | 13   | 611    | 35  |
| IK 410-1000                  | 10               | 7 x 19 | M16               | +48   -90              | 16,3 | 14,5 | 772    | 52  |
| IK 410-1200                  | 12               | 7 x 19 | M20               | +60   -105             | 19,3 | 19,5 | 888    | 75  |

kN = Bruchkraft\_kN = breaking load

All dimensions in millimeters.