



Artikelnummer Part number	a	b	e	f	g	ø d	ø d1	ø Seil ø rope	Spannweg Adjustment	l1	l2	ø l
670-0600	M10	231	14	18	10	12,5	10	6	+13 -43	8	17	10,3
670-0800	M12	307	16	24	12	16,1	12	8	+22 -58	10	20	12,3
670-1000	M14	346	20	29	14	17,8	16	10	+31 -73	12	26	16,3
670-1200	M16	458	25	35	17	21,4	20	12	+39 -87	15	33	20,3
670-1400	M20	535	28	41	20	24,9	23	14	+46 -106	18	38	23,3
670-1600	M24	644	33	48	22	28	26	16	+60 -126	20	42	26,3
670-1800	M27	712	38	53	28	34,5	29	18	+54 -135	25	48	29,3
670-2200	M30	850	40	61	30	40,3	33	22	+74 -164	25	56	33,3
670-2600	M36	913	45	71	33	45,9	36	26	+56 -164	30	60	36,3

Werkstoff 1.4404 | Europäische Technische Zulassung erteilt | Bruchkraft siehe Kapiteleinstieg "Zulassungen"

Material AISI 316L | European Technical Approval granted | for breaking load see introduction of the chapter "Approvals"

All dimensions in millimeters.